arXiv:1110.4054v1 [physics.flu-dyn] 18 Oct 2011

Chimney Formation in Mushy Layers – Experiment and Simulation

Anthony M. Anderson[1], Richard F. Katz[2], and Grae Worster[1]

[1]Department of Applied Math and Theoretical Physics,
University of Cambridge, Cambridge, UK

[2]Department of Earth Sciences,
University of Oxford, Oxford, UK

20–22 November, 2011

Abstract

In this fluid dyanmics video, we show experimental images and simulations of chimney formation in mushy layers. A directional solidification apparatus was used to freeze 25 wt% aqueous ammonium chloride solutions at controlled rates in a narrow Hele-Shaw cell (1mm gap). The convective motion is imaged with schlieren. We demonstrate the ability to numerically simulate mushy layer growth for direct comparison with experiments.

Mushy layers come into being during the rapid solidification of binary liquid melts. They are composed of aligned dendritic crystals that are bathed in residual liquid. This residual interstitial liquid is typically of a different composition than the bulk liquid, which can trigger convection within the mushy layer. When convection is present, dissolution often leads to the formation of chimneys – drainage channels devoid of solid. Chimneys are the source of defects known as freckles in industrial casting processes. Chimneys are also conduits for brine drainage from young sea ice. A major goal in the study of mushy layers is to predict the formation of chimneys and the amount of solute transported through them.

We have used a directional solidification apparatus to conduct experiments on aqueous ammonium chloride (NH_4 Cl) at fixed freezing rates in a Hele-Shaw cell with a 1 mm gap thickness. Since the solution concentrations used were larger than the eutectic concentration and freezing was from below, the interstitial fluid in the mushy layer was lighter and fresher than the surrounding fluid, producing double-diffusive convection. Using schlieren, we imaged the density field to reveal the convective fluid motion and chimney formation for a range of freezing rates and starting concentrations. An experimental video is shown for a 25 wt% solution frozen at 1 μm/s.

A mushy layer can be modeled as a reactive porous matrix whose porosity changes in order to ensure local thermodynamic equilibrium. The use of a Hele-Shaw cell with a narrow gap in the above experiments greatly simplifies the modelling of mushy layers since Darcy's Law can be used throughout the entire domain. Katz and Worster (J. Comp. Phys, 2008) developed a 2D numerical model based on this simplification and the Enthalpy method. With this approach, the prescription of internal boundary conditions at the solid, mush, and liquid interfaces could be avoided. With these simulations, we have the opportunity to make direct comparisons with experiments. This capability is demonstrated in a simulation video using the same conditions as in the experimental video.